

**M12 male 0° / M12 female 90° A-cod. LED**

PUR 4x0.34 ye UL/CSA 10m

**⚠ NOTICE ⚠****PRODUCT IS DISCONTINUED. PLEASE HAVE A LOOK AT THE ALTERNATIVE PRODUCTS.**

Male straight – female 90°

M12 – M12, 4-pole





3× LED (PNP), (NPN) on request



Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link naar het product](#)**Afbeelding**



Product van afwijken van afbeelding



|                                           |                   |
|-------------------------------------------|-------------------|
| Cable length                              | 10 m              |
| Side 1                                    |                   |
| Tightening torque                         | 0,6 Nm            |
| Mounting method                           | inserted, screwed |
| Family construction form                  | M12               |
| Thread                                    | M12 x 1           |
| suitable for corrugated tube (internal Ø) | 10 mm             |
| Material                                  | PUR               |
| Width across flats                        | SW13              |
| Degree of protection (EN IEC 60529)       | IP65, IP66K, IP67 |
| Side 2                                    |                   |
| Tightening torque                         | 0,6 Nm            |
| Mounting method                           | inserted, screwed |
| Family construction form                  | M12               |
| Thread                                    | M12 x 1           |
| suitable for corrugated tube (internal Ø) | 10 mm             |
| Material                                  | PUR               |
| Width across flats                        | SW13              |
| Degree of protection (EN IEC 60529)       | IP65, IP66K, IP67 |
| Commerciële gegevens                      |                   |
| ECLASS-6.0                                | 27279218          |
| ECLASS-6.1                                | 27279218          |
| ECLASS-7.0                                | 27279218          |
| ECLASS-8.0                                | 27279218          |
| ECLASS-9.0                                | 27060311          |
| ECLASS-10.1                               | 27060311          |
| ECLASS-11.1                               | 27060311          |
| ECLASS-12.0                               | 27060311          |
| ETIM-5.0                                  | EC001855          |
| Douane tarief nummer                      | 85444290          |
| GTIN                                      | 4048879170314     |
| Verpakkingseenheid                        | 1                 |
| Electrical data   Supply                  |                   |

|                                                 |                                                                                        |
|-------------------------------------------------|----------------------------------------------------------------------------------------|
| Operating voltage DC                            | 24 V                                                                                   |
| Operating voltage DC min.                       | 18 V                                                                                   |
| Operating voltage DC max.                       | 30 V                                                                                   |
| Operating voltage DC max. (UL-listed)           | 30 V                                                                                   |
| Current operating per contact max.              | 4 A                                                                                    |
| <b>Diagnostics</b>                              |                                                                                        |
| Status indication LED                           | green, white, yellow                                                                   |
| <b>Installation   Connection</b>                |                                                                                        |
| Mounting set                                    | M12 x 1                                                                                |
| <b>Device protection   Electrical</b>           |                                                                                        |
| Additional condition protection degree          | inserted, screwed                                                                      |
| Pollution Degree                                | 3                                                                                      |
| Rated surge voltage                             | 0,8 kV                                                                                 |
| Material group (IEC 60664-1)                    | I                                                                                      |
| <b>Mechanical data   Material data</b>          |                                                                                        |
| Coating locking                                 | Nickeled                                                                               |
| Coating of fitting                              | nickel plated                                                                          |
| Locking material                                | Zinc die-casting                                                                       |
| Material screw connection                       | Zinc die-casting                                                                       |
| <b>Mechanical data   Mounting data</b>          |                                                                                        |
| Mounting method                                 | inserted, screwed, Shaking protection                                                  |
| <b>Environmental characteristics   Climatic</b> |                                                                                        |
| Operating temperature min.                      | -25 °C                                                                                 |
| Operating temperature max.                      | 85 °C                                                                                  |
| Additional condition temperature range          | depending on cable quality                                                             |
| <b>Conformity</b>                               |                                                                                        |
| Product standard                                | DIN EN 61076-2-101 (M12)                                                               |
| <b>Installation   Cable</b>                     |                                                                                        |
| Cable identification                            | 282                                                                                    |
| Jacket Color                                    | blue                                                                                   |
| Amount stranding                                | 1                                                                                      |
| Stranding                                       | 3 wires twisted                                                                        |
| Amount stranding (type 2)                       | 1                                                                                      |
| Stranding (type 2)                              | 9 wires around Stranding combination twisted                                           |
| Banding                                         | Fleece                                                                                 |
| wire arrangement                                | gray-pink, violet, red-blue, brown, red, gray, black, yellow, pink, green, white, blue |
| No. of bending cycles (C-track)                 | 4 Mio. @ 25 °C                                                                         |
| Cable weight                                    | 44 g/m                                                                                 |
| Material jacket                                 | TPE-S                                                                                  |
| Shore hardness jacket                           | 47 ± 5 Shore D                                                                         |
| Freedom from ingredients (jacket)               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                         |
| Outer-diameter (jacket)                         | 6 mm                                                                                   |
| Tolerance outer diameter (sheath)               | ± 5 %                                                                                  |
| Material wire insulation                        | PP                                                                                     |
| Amount wires                                    | 12                                                                                     |
| Outer diameter insulation                       | 1 mm                                                                                   |
| Outer diameter tolerance core insulation        | ± 5 %                                                                                  |
| Shore hardness wire insulation                  | 64 ± 3 Shore D                                                                         |
| Ingredient freeness wire insulation             | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                         |
| Amount strands (wire)                           | 18                                                                                     |
| Diameter of single wires                        | 0,1 mm                                                                                 |

|                                          |                                                      |
|------------------------------------------|------------------------------------------------------|
| Conductor crosssection (wire)            | 0,14 mm <sup>2</sup>                                 |
| Material conductor wire                  | Stranded copper wire, bare                           |
| Conductor type (wire)                    | strand class 6                                       |
| Traversing distance (C-track)            | 10 m @ 25 °C   horizontal                            |
| Current load capacity (standard)         | to DIN VDE 0298-4                                    |
| Current load capacity min. wire          | 2 A                                                  |
| Electrical resistance line constant wire | 139 Ω/km @ 20 °C                                     |
| Nominal voltage power AC max.            | 300 V                                                |
| AC withstand voltage power (wire - wire) | 3 kV @ 60 s                                          |
| Min. operating temperature (static)      | -40 °C                                               |
| Max. operating temperature (fixed)       | 105 °C                                               |
| Operating temperature min. (dynamic)     | -25 °C                                               |
| Operating temperature max. (dynamic)     | 105 °C                                               |
| Flame resistance                         | IEC 60332-2-2   UL 1581 § 1090   UL 1581 § 1100 FT2  |
| chemical resistance                      | Good, application-related testing                    |
| Gasoline resistance                      | Good, application-related testing                    |
| Oil resistance                           | Good, application-related testing   DIN EN 60811-404 |
| Bending radius (fixed)                   | 5 x Outer diameter                                   |
| Bending radius (dynamic)                 | 10 x Outer diameter                                  |
| No. of torsion cycles                    | 2 Mio.                                               |
| Torsion speed                            | 35 cycles/min                                        |
| Torsion stress                           | ± 180 °/m                                            |