MURR ELEKTRONIK
stay connected

ALLEN-BRADLEY CONTACTOR SUPPRESSOR


Varistor, 24VAC/DC


24 V AC/DC
VDR
For other configurations and voltages, please inquire.

Link to Product

Illustration







Product may differ from Image

Commercial data

ECLASS-6.0	27371013
customs tariff number	85363010
GTIN	4048879017848
Packaging unit	1

Compatibility | Compatible with

Appropriate contactors	100-M

Electrical data

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28

Damping factor	1.5× UN
Electrical data | Input	
Input voltage AC min.	24 V
Input voltage AC max.	30 V
Input voltage DC min.	24 V
Input voltage DC max.	30 V
Installation | Connection	
Connection information	flexible connection wires
Device protection | Media	
Flame resistance	flame retardant
Mechanical data | Material data	
Combustibility class housing (UL94)	V-0
Material housing	Plastic
Mechanical data | Mounting data	
Height	20 mm
Width	10 mm
Depth	32 mm
Environmental characteristics | Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	70 °C

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28