

CUBE20 POTENTIAL TERMINAL BLOCK 4xBROWN

Potential terminal block

[Link to Product](#)

Illustration



Product may differ from Image



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27141106      |
| ECLASS-7.0                               | 27141106      |
| ECLASS-8.0                               | 27141106      |
| ECLASS-9.0                               | 27141106      |
| ETIM-5.0                                 | EC001283      |
| customs tariff number                    | 85369010      |
| GTIN                                     | 4048879567459 |
| Packaging unit                           | 1             |
| Electrical data   Supply                 |               |
| Operating voltage AC max.                | 30 V          |
| Operating voltage DC max.                | 30 V          |
| Total current max.                       | 10 A          |
| Device protection   Electrical           |               |
| Degree of protection (EN IEC 60529)      | IP20          |
| Mechanical data   Mounting data          |               |
| Height                                   | 70 mm         |
| Width                                    | 56 mm         |
| Depth                                    | 32,5 mm       |
| Environmental characteristics   Climatic |               |
| Operating temperature min.               | 0 °C          |
| Operating temperature max.               | 55 °C         |
| Storage temperature min.                 | -40 °C        |
| Storage temperature max.                 | 85 °C         |
| Connection type 1                        |               |

|                          |                           |
|--------------------------|---------------------------|
| Connection type 1        | X3                        |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | colorless                 |
| No. of poles             | 10                        |
| PIN 1                    | 24 V DC                   |
| PIN 2                    | 24 V DC                   |
| PIN 3                    | 24 V DC                   |
| PIN 4                    | 24 V DC                   |
| PIN 5                    | 24 V DC                   |
| PIN 6                    | 24 V DC                   |
| PIN 7                    | 24 V DC                   |
| PIN 8                    | 24 V DC                   |
| PIN 9                    | 24 V DC                   |
| PIN 10                   | 24 V DC                   |