MURR ELEKTRONIK
stay connected

# CUBE20S DIGITAL INPUT MODULE DI2


2x24VDC Time Stamp ETS

Expansion module
DI2 - (E) ETS

## Link to Product

### Illustration






Product may differ from Image

| Commercial data | |
|---|---|
| ECLASS-6.0 | 27242604 |
| ECLASS-7.0 | 27242604 |
| ECLASS-8.0 | 27242604 |
| ECLASS-9.0 | 27242604 |
| ETIM-5.0 | EC001599 |
| customs tariff number | 85389099 |
| GTIN | 4048879423410 |
| Packaging unit | 1 |

| Electrical data \| Supply | |
|---|---|
| Norm operating voltage | EN 61131-2 |
| Operating voltage US DC | 24 V |
| Current consumption max. | 85 mA |
| module supply | via system connection |

| Electrical data \| Input | |
|---|---|
| Type input | PNP (EN 61131-2) |
| Input time filter max. | 1,0E-4 ms |
| Current carrying capacity max. | 0,5 A |

| Diagnostics | |
|---|---|
| Diagnostic | No voltage |
| Diagnostic via BUS | per module |
| Diagnostic via LED | per module and channel |
| Short circuit diagnosis | yes |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28

| | |
|---|---|
| LED display | Ethernet connection/data traffic |
| Overload diagnosis | yes |
| **Device protection \| Electrical** | |
| Degree of protection (EN IEC 60529) | IP20 |
| Galvanic separation (operating voltage) | yes |
| Galvanic separation input/input | yes |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height | 109 mm |
| Width | 12,9 mm |
| Depth | 76,5 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | 0 °C |
| Operating temperature max. | 60 °C |
| Storage temperature min. | -20 °C |
| Storage temperature max. | 70 °C |
| **Connection type 2** | |
| Connection type 1 | Power |
| Connection type 2 | Power |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| No. of poles | 8 |
| PIN 1 | n.c. |
| PIN 2 | 24 V DC |
| PIN 3 | 0 V |
| PIN 4 | 24 V DC Sys |
| PIN 5 | n.c. |
| PIN 6 | 24 V DC |
| PIN 7 | 0 V |
| PIN 8 | 0 V Sys |
| Connection | Spring clamp terminals FK |
| Family construction form | terminal |
| Gender | female |
| No. of poles | 8 |
| PIN 1 | DI 0 |
| PIN 2 | 24 V DC |
| PIN 3 | 0 V |
| PIN 5 | DI 1 |
| PIN 6 | 24 V DC |
| PIN 7 | 0 V |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28