

EUROCARD HOLDER

SKPD form D, 230V, 32-pole, 234x160mm

screw terminal 32-pole 230 V AC

To insert the card first press down the 2 yellow buttons. Then slide the Eurocard into the guide slots pushing until fully engaged. The card is now locked into position. It can be removed by pressing down on the 2 yellow buttons.

Link to Product

Illustration



Product may differ from Image



| Commercial data | |
|--|-------------------|
| ECLASS-6.0 | 27260710 |
| ECLASS-6.1 | 27260704 |
| ECLASS-7.0 | 27440402 |
| ECLASS-8.0 | 27440402 |
| ECLASS-9.0 | 27440402 |
| ECLASS-10.1 | 27440402 |
| ECLASS-11.1 | 27460201 |
| ECLASS-12.0 | 27460201 |
| ETIM-5.0 | EC002780 |
| customs tariff number | 85366990 |
| GTIN | 4048879040051 |
| Packaging unit | 1 |
| Electrical data Supply | |
| Operating voltage AC | 230 V |
| Operating current max. | 4 A |
| Installation | |
| Connection cross-section solid min. | 0,25 mm² |
| Connection cross-section solid max. | 4 mm ² |
| Connection cross-section stranded/fine- stranded min. | 0,5 mm² |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-17

Connection cross-section stranded/fine-

Material housing



2,5 mm² stranded max. Installation | Connection Connection Screw terminals SK Installation | Pin assignment 32 No. of poles Device protection | Media Flame resistance flame retardant Mechanical data | Material data

| Mechanical data Mounting data | | |
|---------------------------------|---------------|--|
| Mounting method | screwed | |
| Suitable for mounting type | mounting rail | |
| Height | 63 mm | |
| Width | 274 mm | |
| Depth | 167 mm | |

Plastic