

MODLINK MSDD DATA INSERT

1×USB-A fem./male 0,7m cable + 1×SUB-D25 fem./male

USB (form A); SUB-D25  
1× USB 2.0 (female/female/0.7 m cable) form A  
1× SUB-D25 (female/male)

Link to Product

Illustration



Product may differ from Image



| Commercial data                          |                  |
|------------------------------------------|------------------|
| ECLASS-6.0                               | 27189217         |
| ECLASS-6.1                               | 27189217         |
| ECLASS-7.0                               | 27189217         |
| ECLASS-8.0                               | 27189217         |
| ECLASS-9.0                               | 27189217         |
| ECLASS-10.1                              | 27182806         |
| ECLASS-11.1                              | 27182806         |
| ECLASS-12.0                              | 27182806         |
| ETIM-5.0                                 | EC002625         |
| customs tariff number                    | 85366990         |
| GTIN                                     | 4048879037747    |
| Packaging unit                           | 1                |
| Mechanical data   Mounting data          |                  |
| Height                                   | 88 mm            |
| Width                                    | 51 mm            |
| Depth                                    | 45 mm            |
| Environmental characteristics   Climatic |                  |
| Storage temperature min.                 | -30 °C           |
| Storage temperature max.                 | 60 °C            |
| Shielding plate                          |                  |
| Connection information                   | Threaded hole M4 |

Tightening torque 0,9 Nm

#### USB

|                                  |                   |
|----------------------------------|-------------------|
| Operating voltage AC             | 48 V              |
| Operating voltage DC             | 48 V              |
| Operating voltage DC (UL-listed) | 42,4 V            |
| Operating current max.           | 500 mA            |
| USB specification                | 2.0               |
| Data transmission rate max.      | 480 MBit/s        |
| Looking techniques               | Snap-in connector |

#### SUB-D25

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D25                                        |
| Family type Back side                 | SUB-D25                                        |
| Gender                                | female                                         |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 25                                             |