

MODLINK MSDD DATA INSERT

1xUSB-A female/female + 1xRJ45

USB (form A); RJ45  
1× USB 3.0 (female/female) form A  
1× RJ45, 8-pole metal, CAT5e (female/female)

Link to Product

Illustration



Product may differ from Image



| Commercial data                          |                  |
|------------------------------------------|------------------|
| ECLASS-6.0                               | 27189217         |
| ECLASS-6.1                               | 27189217         |
| ECLASS-7.0                               | 27189217         |
| ECLASS-8.0                               | 27189217         |
| ECLASS-9.0                               | 27189217         |
| ECLASS-10.1                              | 27182806         |
| ECLASS-11.1                              | 27182806         |
| ECLASS-12.0                              | 27182806         |
| ETIM-5.0                                 | EC002625         |
| customs tariff number                    | 85366990         |
| GTIN                                     | 4048879037587    |
| Packaging unit                           | 1                |
| Mechanical data   Mounting data          |                  |
| Height                                   | 88 mm            |
| Width                                    | 51 mm            |
| Depth                                    | 70,4 mm          |
| Environmental characteristics   Climatic |                  |
| Storage temperature min.                 | 5 °C             |
| Storage temperature max.                 | 40 °C            |
| Shielding plate                          |                  |
| Connection information                   | Threaded hole M4 |

Tightening torque 0,9 Nm

**USB**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC                  | 48 V              |
| Operating voltage DC                  | 48 V              |
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Operating current                     | 1,5 A             |
| USB specification                     | 3.0               |
| Data transmission rate max.           | 5000 MBit/s       |
| Looking techniques                    | Snap-in connector |

**RJ45**

|                                       |                   |
|---------------------------------------|-------------------|
| Operating voltage AC max. (UL-listed) | 30 V              |
| Operating voltage DC max. (UL-listed) | 42,4 V            |
| Current operating max. (UL)           | 175 mA            |
| Family construction form              | RJ45              |
| Family type Back side                 | RJ45              |
| Cable category min.                   | Cat5e             |
| Looking techniques                    | Snap-in connector |