

Signal tower Modlight50 Pro equipped with LED modules

green,amber,red,buzzer

Basic, buzzer, flash + LED modules  
green, yellow, red

Link to Product

Illustration



Product may differ from Image



| Commercial data                |               |
|--------------------------------|---------------|
| ECLASS-6.0                     | 27371230      |
| ECLASS-6.1                     | 27371230      |
| ECLASS-7.0                     | 27371230      |
| ECLASS-8.0                     | 27371230      |
| ECLASS-9.0                     | 27371230      |
| ECLASS-10.1                    | 27371230      |
| ECLASS-11.1                    | 27371230      |
| ECLASS-12.0                    | 27371230      |
| ETIM-5.0                       | EC001042      |
| customs tariff number          | 85318070      |
| GTIN                           | 4048879759656 |
| Packaging unit                 | 1             |
| Electrical data   Supply       |               |
| Operating voltage DC           | 24 V          |
| Operating voltage DC min.      | 21,6 V        |
| Operating voltage DC max.      | 26,4 V        |
| Current consumption max.       | 385 mA        |
| Industrial communication   HMI |               |
| Reduced sound pressure at 1 m  | 80 dB         |
| Sound pressure at 1 m          | 90 dB         |
| HMI   Illumination properties  |               |

Blink cycles 60 ±12 per minute

**Device protection | Electrical**

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

**Mechanical data | Material data**

|                  |         |
|------------------|---------|
| Color housing    | black   |
| Material housing | Plastic |

**Mechanical data | Mounting data**

|        |          |
|--------|----------|
| Height | 253,5 mm |
| Width  | 50 mm    |
| Depth  | 50 mm    |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 60 °C  |