

Cable drum Ø 355mm

PVC 3x0.34 bk UL/CSA 100m

Cable drum (100 m)  
PVC (UL/CSA)  
3× 0.34 mm², black

Link to Product

Illustration



Product may differ from Image



| Commercial data       |                    |
|-----------------------|--------------------|
| ECLASS-6.0            | 27062011           |
| ECLASS-6.1            | 27061801           |
| ECLASS-7.0            | 27061801           |
| ECLASS-8.0            | 27061801           |
| ECLASS-9.0            | 27061801           |
| ECLASS-10.1           | 27061801           |
| ECLASS-11.1           | 27061801           |
| ECLASS-12.0           | 27061801           |
| ETIM-5.0              | EC001855           |
| customs tariff number | 85444995           |
| GTIN                  | 4048879315012      |
| Packaging unit        | 1                  |
| Installation   Cable  |                    |
| Cable identification  | 613                |
| Cable Type            | 1                  |
| Jacket Color          | black              |
| Type of Certificate   | cURus              |
| Amount stranding      | 1                  |
| Stranding             | 3 wires twisted    |
| wire arrangement      | brown, black, blue |
| Cable weighth         | 34,1 g/m           |

|                                                   |                                                      |
|---------------------------------------------------|------------------------------------------------------|
| Material jacket                                   | PVC                                                  |
| Shore hardness jacket                             | 85 ± 5 Shore A                                       |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, silicone-free     |
| Outer-diameter (jacket)                           | 4,6 mm                                               |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                |
| Material wire insulation                          | PVC                                                  |
| Amount wires                                      | 3                                                    |
| Outer diameter insulation                         | 1,25 mm                                              |
| Outer diameter tolerance core insulation          | ± 5 %                                                |
| Shore hardness wire insulation                    | 45 ± 5 Shore D                                       |
| Material properties wire insulation               | good machinability                                   |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, silicone-free     |
| Amount strands (wire)                             | 19                                                   |
| Diameter of single wires                          | 0,15 mm                                              |
| Conductor crosssection (wire)                     | 0,34 mm <sup>2</sup>                                 |
| Material conductor wire                           | Stranded copper wire, bare                           |
| Conductor type (wire)                             | Strand class 5                                       |
| Nominal voltage AC max.                           | 300 V                                                |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                    |
| Current load capacity min. wire                   | 6 A                                                  |
| Electrical resistance line constant wire          | 57 Ω/km @ 20 °C                                      |
| AC withstand voltage (wire - wire)                | 2 kV @ 60 s                                          |
| Power frequency withstand voltage (wire - jacket) | 2 kV @ 60 s                                          |
| Min. operating temperature (static)               | -30 °C                                               |
| Max. operating temperature (fixed)                | 80 °C                                                |
| Operating temperature min. (dynamic)              | -5 °C                                                |
| Operating temperature max. (dynamic)              | 80 °C                                                |
| UV resistance                                     | DIN EN ISO 4892-2 A                                  |
| Flame resistance                                  | IEC 60332-2-2   UL 1581 § 1100 FT2   UL 1581 § 1090  |
| chemical resistance                               | Good, application-related testing                    |
| Gasoline resistance                               | Good, application-related testing                    |
| Oil resistance                                    | Good, application-related testing   DIN EN 60811-404 |
| Bending radius (fixed)                            | 5 x Outer diameter                                   |
| Bending radius (dynamic)                          | 10 x Outer diameter                                  |