


B6 Hood, IP68

Screw locking, top entry M32

B6
Hood
Screw locking
IP68
Technical data will be only guaranteed with Murrelektronik components.

Link to Product

Illustration



Product may differ from Image

Commercial data	
ECLASS-6.0	27143424
ECLASS-6.1	27261203
ECLASS-7.0	27440202
ECLASS-8.0	27440202
ECLASS-9.0	27440202
ECLASS-10.1	27440202
ECLASS-11.1	27440202
ECLASS-12.0	27440202
ETIM-5.0	EC000437
customs tariff number	85389099
GTIN	4048879647342
Packaging unit	1
Installation	
Cable outlet	straight
Installation Connection	
Tightening torque	4 Nm
Mounting set	M32
Mating cycles min.	500
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP68
Additional condition protection degree	inserted, locked, with screw connection
Mechanical data	
Housing type	Hood

Mechanical data | Material data

Coating housing	powder-coated
Material gasket	Silicon
Material housing	Aluminum die casting
Locking material	Stainless steel

Mechanical data | Mounting data

Size	B6
Mounting method	Screw locking
Height	100,5 mm
Width	58 mm
Depth	132 mm

Environmental characteristics | Climatic

Operating temperature min.	-40 °C
Operating temperature max.	125 °C
Climatic category (EN IEC 60068-1)	40/125/21