

## MODL.VARIO Accessories closure plug 4/2

for adaptive inserts, nickel plated brass

Modlink Vario Accessories Locking plug Diameter 4 mm Quantity: 10 pcs. good resistance to oil, gasoline and chemicals The resistance to aggressive media should be individually tested for your application. Further details on request.

## Link to Product

Illustration



Product may differ from Image

| Commercial data                 |               |  |
|---------------------------------|---------------|--|
| ECLASS-6.0                      | 27260702      |  |
| ECLASS-6.1                      | 27269202      |  |
| ECLASS-7.0                      | 27449203      |  |
| ECLASS-8.0                      | 27449203      |  |
| ECLASS-9.0                      | 27440192      |  |
| ECLASS-10.1                     | 27440192      |  |
| ECLASS-11.1                     | 27440192      |  |
| ECLASS-12.0                     | 27440192      |  |
| ETIM-5.0                        | EC002641      |  |
| customs tariff number           | 85389099      |  |
| GTIN                            | 4048879618878 |  |
| Packaging unit                  | 10            |  |
| Mechanical data                 |               |  |
| Operating pressure min.         | -0,8 bar      |  |
| Operating pressure max.         | 16 bar        |  |
| Mechanical data   Material data |               |  |
| Coating housing                 | nickel plated |  |
| Material housing                | Brass         |  |
| Mechanical data   Mounting data |               |  |
| Size                            | AD4           |  |
| Height                          | 19 mm         |  |

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-04-24

Murrelektronik B.V. | Takkebijsters 3 | 4817 BL Breda | Fon 085-22 20 282 | Fax 085-22 20 283 | shop@murrelektronik.nl | shop.murrelektronik.nl



| Width                                    | 5,5 mm |  |  |  |
|--|--------|--|--|--|
| Depth                                    | 5,5 mm |  |  |  |
| Environmental characteristics   Climatic |        |  |  |  |
| Operating temperature min.               | -20 °C |  |  |  |
| Operating temperature max.               | 120 °C |  |  |  |