

MODL. VARIO insert for fixed housing type B

6/4 shut-off, nickel plated brass


Insert - stationary housing  
Brass, nickel plated  
with shut-off  
AD6

Link to Product

Illustration



Product may differ from Image



Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27260702      |
| ECLASS-6.1            | 27260708      |
| ECLASS-7.0            | 27440312      |
| ECLASS-8.0            | 27440312      |
| ECLASS-9.0            | 27440312      |
| ECLASS-10.1           | 27440312      |
| ECLASS-11.1           | 27440312      |
| ECLASS-12.0           | 27440312      |
| ETIM-5.0              | EC002641      |
| customs tariff number | 74198090      |
| GTIN                  | 4048879573764 |
| Packaging unit        | 1             |

Device protection | Electrical

|                                        |                   |
|----------------------------------------|-------------------|
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68  |
| Degree of protection (ISO 20653:2013)  | IP66K, IP69K      |
| Additional condition protection degree | inserted, screwed |

Mechanical data

|                         |               |
|-------------------------|---------------|
| Barrier                 | with shut-off |
| Operating pressure min. | 0 bar         |
| Operating pressure max. | 16 bar        |

Mechanical data | Material data

|                  |               |
|------------------|---------------|
| Coating housing  | nickel plated |
| Material gasket  | FPM           |
| Material housing | Brass         |

**Mechanical data | Mounting data**

Outer diameter hose 6 mm

**Environmental characteristics | Climatic**

Operating temperature min. -20 °C

---

Operating temperature max. 120 °C