

PROFIBUS-PLUG-MALE (SUB-D) 90°

Cut clamp for rigid and flexible wires

Bus connection plug 90°  
PROFIBUS  
SUB-D9 (male), IDC terminals, rigid and flexible cable, programming device connection  
PROFIBUS, FC cable rigid/flexible, 1× 2× 0.64 mm², for outer diameter 8.0 ±0.5 mm

Link naar het product

Afbeelding



Product van afwijken van afbeelding



| Commerciële gegevens        |                         |
|-----------------------------|-------------------------|
| ECLASS-6.0                  | 27279221                |
| ECLASS-7.0                  | 27440104                |
| ECLASS-8.0                  | 27440104                |
| ECLASS-9.0                  | 27440102                |
| ECLASS-10.1                 | 27242692                |
| ECLASS-11.1                 | 27242692                |
| ECLASS-12.0                 | 27242692                |
| ETIM-5.0                    | EC001855                |
| Douane tarief nummer        | 85389091                |
| GTIN                        | 4048879050562           |
| Verpakkingseenheid          | 1                       |
| Electrical data             |                         |
| Terminating resistor        | connectable, integrated |
| Electrical data   Supply    |                         |
| Operating voltage DC min.   | 4,75 V                  |
| Operating voltage DC max.   | 5,25 V                  |
| Current consumption max.    | 12,5 mA                 |
| Industrial communication    |                         |
| Data transmission rate max. | 12 MBit/s               |
| Installation   Connection   |                         |

Connection Cut clamps IDC

**Device protection | Electrical**

|                                     |      |
|-------------------------------------|------|
| Degree of protection (EN IEC 60529) | IP20 |
| Pollution Degree                    | 2    |

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 72 mm |
| Width  | 40 mm |
| Depth  | 17 mm |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -25 °C |
| Operating temperature max. | 60 °C  |
| Storage temperature min.   | -25 °C |
| Storage temperature max.   | 80 °C  |