

10 Port unmanaged Gigabit Switch 4 PoE 2 SFP Ports IP20 metal

10 Port Unmanaged IP20 PoE Gigabit Switch Metal  
24 V power supply  
4 PoE ports – 2 SFP ports

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



| Commerciële gegevens                              |               |
|---------------------------------------------------|---------------|
| ECLASS-6.1                                        | 19170106      |
| ECLASS-7.0                                        | 19170106      |
| ECLASS-8.0                                        | 19170106      |
| ECLASS-9.0                                        | 19170402      |
| ECLASS-10.1                                       | 19170402      |
| ECLASS-11.1                                       | 19170402      |
| ECLASS-12.0                                       | 19170402      |
| Douane tarief nummer                              | 85176200      |
| GTIN                                              | 4048879844215 |
| Verpakkingseenheid                                | 1             |
| Electrical data   Supply                          |               |
| Operating voltage DC min.                         | 12 V          |
| Operating voltage DC max.                         | 57 V          |
| PoE voltage amplifier                             | yes           |
| Industrial communication                          |               |
| Data transmission rate max.                       | 1000 MBit/s   |
| Industrial communication   Ethernet functionality |               |
| Auto-crossover                                    | yes           |
| Auto-negotiation                                  | yes           |
| duplex                                            | Full duplex   |
| Switch type                                       | unmanaged     |
| VLAN unmanaged (IEEE 802.1Q)                      | yes           |

| Diagnostics                              |                                  |
|------------------------------------------|----------------------------------|
| Alarm contact                            | yes                              |
| Diagnostic                               | No voltage                       |
| LED display                              | Ethernet connection/data traffic |
| Device protection   Electrical           |                                  |
| Degree of protection (EN IEC 60529)      | IP20                             |
| Mechanical data   Material data          |                                  |
| Color housing                            | black                            |
| Material housing                         | Metal                            |
| Mechanical data   Mounting data          |                                  |
| Mounting method                          | geschnappt                       |
| Suitable for mounting type               | Mounting rail TH35, (EN 60715)   |
| Height                                   | 145 mm                           |
| Width                                    | 57,8 mm                          |
| Depth                                    | 113 mm                           |
| Environmental characteristics   Climatic |                                  |
| Operating temperature min.               | -40 °C                           |
| Operating temperature max.               | 70 °C                            |
| Storage temperature min.                 | -40 °C                           |
| Storage temperature max.                 | 85 °C                            |
| Connection type 3                        |                                  |
| Connection type 1                        | 8                                |
| Connection type 2                        | 10                               |
| Connection type 3                        | X1                               |
| Family construction form                 | RJ45                             |
| Gender                                   | female                           |
| Color contact carrier                    | black                            |
| No. of poles                             | 8                                |
| PIN 1                                    | TD +                             |
| PIN 2                                    | TD -                             |
| PIN 3                                    | RD +                             |
| PIN 4                                    | n.c.                             |
| PIN 5                                    | n.c.                             |
| PIN 6                                    | RD -                             |
| PIN 7                                    | n.c.                             |
| PIN 8                                    | n.c.                             |
| Family construction form                 | POF SC-RJ                        |
| Gender                                   | female                           |
| Color contact carrier                    | black                            |
| No. of poles                             | 2                                |
| PIN 1                                    | RD                               |
| PIN 2                                    | TD                               |
| Connection                               | Plug-in terminals RK             |
| Family construction form                 | terminal                         |
| Gender                                   | male                             |
| Color contact carrier                    | green                            |
| No. of poles                             | 7                                |
| PIN 1                                    | FE                               |
| PIN 2                                    | V 1 -                            |
| PIN 3                                    | V 1 +                            |
| PIN 4                                    | Relay (NO)                       |
| PIN 5                                    | Relay (NO)                       |

|       |       |
|-------|-------|
| PIN 6 | V 2 - |
| PIN 7 | V 2 + |