



Xelity Managed Switch 10x 10/100BT IP67 M12L 5P


10 Port Managed IP67 Fast Ethernet Switch Metal
M12 Power, 5-pole, L-coded
Connection cables are in the online shop under "Connection Technology".

Link naar het product

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens	
ECLASS-6.1	19170106
ECLASS-7.0	19170106
ECLASS-8.0	19170106
ECLASS-9.0	19170401
ECLASS-10.1	19170401
ECLASS-11.1	19170401
ECLASS-12.0	19170401
Douane tarief nummer	85176200

GTIN 4048879862523

Verpakkingseenheid 1

Electrical data | Supply

Operating voltage DC min. 9 V

Operating voltage DC max. 36 V

Industrial communication

Data transmission rate max. 100 MBit/s

Industrial communication | Ethernet functionality

Auto-crossover yes

Auto-negotiation yes

duplex Full duplex

LLDP frames forwarding

Ring topology RSTP, STP

Switch type managed

Industrial communication | IIoT functions

Webserver HTTP, HTTPS

Switch Management

Addressing BOOTP/DHCP client, DCP, SSH-Befehlszeile

NAT 1:1

RSTP (IEEE 802.1D-2004, IEC 62439-1) Default on

Simple Network Management Protocol (SNMP) v1, v2c, v3 (default active)

VLAN managed (IEEE 802.1Q) yes

VLANs max. (IEEE 802.1Q) 64

Time synchronization NTP client

Diagnostics

Alarm contact no

Diagnostic No voltage

Remote maintenance Open VPN client

LED display Ethernet connection/data traffic

Port mirroring 1:1

RMON yes

SNMP traps yes

Syslog yes

Device protection | Electrical

Degree of protection (EN IEC 60529) IP67

Mechanical data | Material data

Material housing Metal

Mechanical data | Mounting data

Suitable for mounting type 2-hole screw mounting

Height 37 mm

Width 63 mm

Depth 225 mm

Environmental characteristics | Climatic

Operating temperature min. -25 °C

Operating temperature max. 70 °C

Derating from 70 °C

Storage temperature min. -40 °C

Storage temperature max. 85 °C

Connection type 3

Connection type 1	XD1
Connection type 2	XD2
Connection type 3	XF2, XF7-XF10
Family construction form	M12
Gender	male
Color contact carrier	gray
Coding	L
No. of poles	5
PIN 1	24 V DC (UB 1) (US)
PIN 2	0 V (UA)
PIN 3	0 V (UB 1) (US)
PIN 4	24 V DC (UA)
PIN 5	PE
Family construction form	M12
Gender	female
Color contact carrier	gray
Coding	L
No. of poles	5
PIN 1	24 V DC (UB 1) (US)
PIN 2	0 V (UA)
PIN 3	0 V (UB 1) (US)
PIN 4	24 V DC (UA)
PIN 5	PE
Family construction form	M12
Gender	female
Color contact carrier	green
Coding	D
No. of poles	4
PIN 1	TD +
PIN 2	RD +
PIN 3	TD -
PIN 4	RD -