

MOTOR SUPPRESSOR



RC, 3x575VAC/5,5kW

3× 400 V AC  
3× 575 V AC  
RC

Suppressors for other voltages, frequencies, and motor ratings available on request. Do not use RC motor suppressors with frequency inverters.

Link naar het product

Afbeelding



Product van afwijken van afbeelding



| Commerciële gegevens |          |
|----------------------|----------|
| ECLASS-6.0           | 27371013 |
| ECLASS-6.1           | 27371013 |
| ECLASS-7.0           | 27371013 |
| ECLASS-8.0           | 27371013 |
| ECLASS-9.0           | 27371013 |

|                      |               |
|----------------------|---------------|
| ECLASS-10.1          | 27371013      |
| ECLASS-11.1          | 27371013      |
| ECLASS-12.0          | 27371013      |
| ETIM-5.0             | EC000197      |
| Douane tarief nummer | 85363010      |
| GTIN                 | 4048879015448 |
| Verpakkingseenheid   | 1             |

**Compatibility | Compatible with**

|                        |                                          |
|------------------------|------------------------------------------|
| Appropriate contactors | 3 RT 20 screw terminals, Siemens 3 RT 10 |
|------------------------|------------------------------------------|

**Electrical data | Supply**

|                 |              |
|-----------------|--------------|
| Power frequency | 50 ... 60 Hz |
|-----------------|--------------|

**Electrical data | Input**

|                  |       |
|------------------|-------|
| Input voltage AC | 575 V |
|------------------|-------|

**Installation | Connection**

|            |                    |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

**Device protection | Media**

|                  |                 |
|------------------|-----------------|
| Flame resistance | flame retardant |
|------------------|-----------------|

**Mechanical data | Material data**

|                                     |                   |
|-------------------------------------|-------------------|
| Combustibility class housing (UL94) | V-0               |
| Material housing                    | Plastic           |
| Material potting compound           | 2-component epoxy |

**Mechanical data | Mounting data**

|                            |                                |
|----------------------------|--------------------------------|
| Mounting method            | geschnappt                     |
| Suitable for mounting type | Mounting rail TH35, (EN 60715) |
| Height                     | 40 mm                          |
| Width                      | 43 mm                          |
| Depth                      | 15 mm                          |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C  |