

MET 1-PHASE CONTROL AND ISOLATION TRANSFORMER

P: 800VA IN: 400VAC+/- 5% OUT: 230VAC

Single-phase - Control and Isolation Transformers  
800 VA  
Spring clamp terminals  
Isolation class T 60/B

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



| Commerciële gegevens |          |
|----------------------|----------|
| ECLASS-6.0           | 27031302 |
| ECLASS-6.1           | 27031302 |
| ECLASS-7.0           | 27031302 |
| ECLASS-8.0           | 27031302 |
| ECLASS-9.0           | 27031302 |
| ECLASS-10.1          | 27031302 |

|                      |               |
|----------------------|---------------|
| ECLASS-11.1          | 27031302      |
| ECLASS-12.0          | 27031302      |
| ETIM-5.0             | EC002486      |
| Douane tarief nummer | 85043180      |
| GTIN                 | 4048879066433 |
| Verpakkingseenheid   | 1             |

**Electrical data | Supply**

|                 |              |
|-----------------|--------------|
| Power frequency | 50 ... 60 Hz |
|-----------------|--------------|

**Electrical data | Input**

|                       |         |
|-----------------------|---------|
| Input voltage AC      | 400 V   |
| Input voltage AC min. | 380 V   |
| Input voltage AC max. | 420 V   |
| Current input AC      | 2,15 A  |
| Max. inrush current   | 30,07 A |
| Short-circuit current | 83,99 A |

**Electrical data | Output**

|                           |        |
|---------------------------|--------|
| Output voltage AC         | 230 V  |
| Output voltage adjustable | no     |
| Power rating AC max.      | 800 VA |

**Device protection | Electrical**

|                                        |      |
|----------------------------------------|------|
| Insulation test voltage input - output | 4 kV |
|----------------------------------------|------|

**Mechanical data | Mounting data**

|                            |                        |
|----------------------------|------------------------|
| Suitable for mounting type | Schlüssellochauhängung |
| Mounting dimension a       | 92 mm                  |
| Mounting dimension b       | 135 mm                 |
| Mounting dimension c       | 7 mm                   |
| Height                     | 118 mm                 |
| Width                      | 175 mm                 |
| Depth                      | 160 mm                 |
| Diameter bore              | 7 mm                   |
| Length bore                | 11 mm                  |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C  |
| Storage temperature min.   | -40 °C |
| Storage temperature max.   | 80 °C  |

**Conformity**

|                  |                                               |
|------------------|-----------------------------------------------|
| Product standard | EN 61558-1, EN 61558-2-4, EN 62041 category 0 |
|------------------|-----------------------------------------------|