

COMLIGHT56 LED BLUE STATUS LIGHT

Input 24VDC

Compact status light  
blue

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27371220      |
| ECLASS-6.1           | 27110390      |
| ECLASS-7.0           | 27110390      |
| ECLASS-8.0           | 27110390      |
| ECLASS-9.0           | 27110350      |
| ECLASS-10.1          | 27110350      |
| ECLASS-11.1          | 27110350      |
| ECLASS-12.0          | 27110350      |
| ETIM-5.0             | EC000232      |
| Douane tarief nummer | 85319000      |
| GTIN                 | 4048879853873 |
| Verpakkingseenheid   | 1             |

Electrical data | Supply

|                          |       |
|--------------------------|-------|
| Operating voltage DC     | 24 V  |
| Current consumption max. | 26 mA |

Industrial communication | HMI

|                    |         |
|--------------------|---------|
| Luminous intensity | 239 mcd |
|--------------------|---------|

Device protection | Electrical

|                                        |                  |
|----------------------------------------|------------------|
| Degree of protection (EN IEC 60529)    | IP65             |
| Additional condition protection degree | inserted, locked |

Mechanical data | Material data

Material housing Plastic

**Mechanical data | Mounting data**

|        |       |
|--------|-------|
| Height | 61 mm |
| Width  | 56 mm |
| Depth  | 56 mm |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -30 °C |
| Operating temperature max. | 50 °C  |

**Connection type 1**

|                          |                           |
|--------------------------|---------------------------|
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| No. of poles             | 2                         |
| PIN 1                    | 24 V DC (0 V)             |
| PIN 2                    | 0 V (24 V DC)             |