

**M12 female 90° A-cod. with cable LED**

PUR 3x0.34 gy UL/CSA 20m

**⚠ NOTICE ⚠****PRODUCT IS DISCONTINUED. PLEASE HAVE A LOOK AT THE ALTERNATIVE PRODUCTS.**

Female 90°

M12, 3-pole





2x LED (PNP)

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link naar het product](#)**Afbeelding**

Product van afwijken van afbeelding



Cable length 20 m

#### Side 1

|                                           |                   |
|-------------------------------------------|-------------------|
| Tightening torque                         | 0,6 Nm            |
| Mounting method                           | inserted, screwed |
| Coating contact                           | gold plated       |
| Family construction form                  | M12               |
| Thread                                    | M12 x 1           |
| suitable for corrugated tube (internal Ø) | 10 mm             |
| Coding                                    | A                 |
| Material contact                          | Copper alloy      |
| Material                                  | PUR               |
| Width across flats                        | SW13              |
| Degree of protection (EN IEC 60529)       | IP65, IP66K, IP67 |

#### Side 2

|                           |             |
|---------------------------|-------------|
| Stripping length (jacket) | 20 mm       |
| Coating contact           | gold plated |

#### Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27279218      |
| ECLASS-6.1           | 27279218      |
| ECLASS-7.0           | 27279218      |
| ECLASS-8.0           | 27279218      |
| ECLASS-9.0           | 27060311      |
| ECLASS-10.1          | 27060311      |
| ECLASS-11.1          | 27060311      |
| ECLASS-12.0          | 27060311      |
| ETIM-5.0             | EC001855      |
| Douane tarief nummer | 85444290      |
| GTIN                 | 4048879204842 |
| Verpakkingseenheid   | 1             |

#### Electrical data | Supply

|                                       |      |
|---------------------------------------|------|
| Operating voltage DC                  | 24 V |
| Operating voltage DC min.             | 18 V |
| Operating voltage DC max.             | 30 V |
| Operating voltage DC max. (UL-listed) | 30 V |
| Current operating per contact max.    | 4 A  |

#### Diagnostics

|                       |               |
|-----------------------|---------------|
| Status indication LED | green, yellow |
|-----------------------|---------------|

#### Installation | Connection

|                           |         |
|---------------------------|---------|
| Stripping length (jacket) | 20 mm   |
| Mounting set              | M12 x 1 |

#### Device protection | Electrical

|                                        |                   |
|----------------------------------------|-------------------|
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 0,8 kV            |
| Material group (IEC 60664-1)           | I                 |

#### Mechanical data | Material data

|                           |                  |
|---------------------------|------------------|
| Coating locking           | Nickeled         |
| Coating of fitting        | nickel plated    |
| Material gasket           | FKM              |
| Locking material          | Zinc die-casting |
| Material screw connection | Zinc die-casting |

| Mechanical data   Mounting data          |                                                                                                                                                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting method                          | inserted, screwed, Shaking protection                                                                                                                  |
| Environmental characteristics   Climatic |                                                                                                                                                        |
| Operating temperature min.               | -25 °C                                                                                                                                                 |
| Operating temperature max.               | 85 °C                                                                                                                                                  |
| Additional condition temperature range   | depending on cable quality                                                                                                                             |
| Important installation notes             |                                                                                                                                                        |
| Note on strain relief                    | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                    |
| Note on bending radius                   | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.  |
| Conformity                               |                                                                                                                                                        |
| Product standard                         | DIN EN 61076-2-101 (M12)                                                                                                                               |
| Cable                                    |                                                                                                                                                        |
| Cable identification                     | 223                                                                                                                                                    |
| Cable Type                               | 2 (PUR/PVC)                                                                                                                                            |
| Approval (cable)                         | UL (AWM-Style 20549/1731), CSA; CE conform                                                                                                             |
| Cable weight [g/m]                       | 35,97 g                                                                                                                                                |
| Material wire                            | Cu wire, bare                                                                                                                                          |
| Resistor (core)                          | max. 57 $\Omega$ /km (20 °C)                                                                                                                           |
| Single wire Ø (core)                     | 0.1 mm                                                                                                                                                 |
| Construction (core)                      | 42× 0.1 mm (multi-strand wire class 6)                                                                                                                 |
| Diameter (core)                          | 3× 0.34 mm <sup>2</sup>                                                                                                                                |
| AWG                                      | similar to AWG 22                                                                                                                                      |
| Material wire isolation                  | PVC                                                                                                                                                    |
| Material property wire insulation        | CFC-, cadmium-, silicone- and lead-free                                                                                                                |
| Shore hardness wire isolation            | 43 ±5 D                                                                                                                                                |
| Wire-Ø incl. isolation                   | 1.25 mm ±5%                                                                                                                                            |
| Color/numbering of wires                 | br, bk, bl                                                                                                                                             |
| Stranding combination                    | 3 wires twisted                                                                                                                                        |
| Shield                                   | no                                                                                                                                                     |
| Material jacket                          | PUR/PVC                                                                                                                                                |
| Material property (jacket)               | CFC-, halogen-, cadmium-, silicone- and lead-free, matt, low-adhesion, machine easy to process, abrasion-resistant, hydrolysis and microbial resistant |
| Shore hardness jacket                    | 80 ±5 A (PVC-under jacket); 85 ±5 A (PUR-jacket)                                                                                                       |
| Outer-Ø (jacket)                         | 4.3 mm ±5%                                                                                                                                             |
| Color jacket                             | gray                                                                                                                                                   |
| chemical resistance                      | good resistance to oil, gasoline and chemicals                                                                                                         |
| Nominal voltage                          | UL 300 V AC                                                                                                                                            |
| Test voltage                             | 2000 V AC                                                                                                                                              |
| Current load capacity                    | to DIN VDE 0298-4                                                                                                                                      |
| Temperature range (fixed)                | -30...+80 °C                                                                                                                                           |
| Temperature range (mobile)               | -5...+80 °C                                                                                                                                            |
| Bending radius (fixed)                   | 10× outer Ø                                                                                                                                            |
| Bending radius (dynamic)                 | 15× outer Ø                                                                                                                                            |
| No. of bending cycles (C-track)          | max. 2 Mio. (25 °C)                                                                                                                                    |
| Travel speed (C-track)                   | max. 3.3 m/s                                                                                                                                           |
| Acceleration (C-track)                   | max. 5 m/s <sup>2</sup>                                                                                                                                |