

M12 female 0° A-cod. with cable

PUR 8x0.25 gy UL/CSA+drag ch. 30m

Female straight  
M12, 8-pole  
Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request  
with cable sleeves  
Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.  
Further cable lengths on request.

Link naar het product

Afbeelding



|   |    |
|---|----|
| 1 | WH |
| 2 | BN |
| 3 | GN |
| 4 | YE |
| 5 | GY |
| 6 | PK |
| 7 | BU |
| 8 | RD |



Product van afwijken van afbeelding



Cable length 30 m

Side 1

Tightening torque 0,6 Nm

|                                                 |                                                                |
|-------------------------------------------------|----------------------------------------------------------------|
| Mounting method                                 | inserted, screwed                                              |
| Family construction form                        | M12                                                            |
| Material                                        | PUR                                                            |
| Width across flats                              | SW13                                                           |
| <b>Commerciële gegevens</b>                     |                                                                |
| ECLASS-6.0                                      | 27279218                                                       |
| ECLASS-7.0                                      | 27279218                                                       |
| ECLASS-8.0                                      | 27279218                                                       |
| ECLASS-9.0                                      | 27060311                                                       |
| ECLASS-10.1                                     | 27060311                                                       |
| ECLASS-11.1                                     | 27060311                                                       |
| ECLASS-12.0                                     | 27060311                                                       |
| ETIM-5.0                                        | EC001855                                                       |
| Douane tarief nummer                            | 85444290                                                       |
| GTIN                                            | 4048879196338                                                  |
| Verpakkingseenheid                              | 1                                                              |
| <b>Electrical data   Supply</b>                 |                                                                |
| Operating voltage AC max.                       | 30 V                                                           |
| Operating voltage DC max.                       | 30 V                                                           |
| <b>Installation   Connection</b>                |                                                                |
| Mounting set                                    | M12 x 1                                                        |
| <b>Device protection   Electrical</b>           |                                                                |
| Pollution Degree                                | 3                                                              |
| Rated surge voltage                             | 0,8 kV                                                         |
| Material group (IEC 60664-1)                    | I                                                              |
| <b>Mechanical data   Material data</b>          |                                                                |
| Coating of fitting                              | nickel plated                                                  |
| Material screw connection                       | Zinc die-casting                                               |
| <b>Environmental characteristics   Climatic</b> |                                                                |
| Operating temperature min.                      | -25 °C                                                         |
| Operating temperature max.                      | 85 °C                                                          |
| Additional condition temperature range          | depending on cable quality                                     |
| <b>Installation   Cable</b>                     |                                                                |
| Cable identification                            | 292                                                            |
| Cable Type                                      | 3                                                              |
| Jacket Color                                    | gray                                                           |
| Type of Certificate                             | cURus                                                          |
| Amount stranding                                | 1                                                              |
| Stranding                                       | 8 wires around Core filler twisted                             |
| Filler                                          | yes                                                            |
| wire arrangement                                | brown, white, red, blue, pink, gray, yellow, green             |
| No. of bending cycles (C-track)                 | 10 Mio. @ 25 °C                                                |
| Cable weight                                    | 52,8 g/m                                                       |
| Material jacket                                 | PUR                                                            |
| Shore hardness jacket                           | 90 ± 5 Shore A                                                 |
| Freedom from ingredients (jacket)               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Outer-diameter (jacket)                         | 5,8 mm                                                         |
| Tolerance outer diameter (sheath)               | ± 5 %                                                          |
| Material wire insulation                        | PP                                                             |
| Amount wires                                    | 8                                                              |
| Outer diameter insulation                       | 1,2 mm                                                         |

|                                                         |                                                                |
|---------------------------------------------------------|----------------------------------------------------------------|
| Outer diameter tolerance core insulation                | ± 5 %                                                          |
| Shore hardness wire insulation                          | 70 ± 5 Shore D                                                 |
| Ingredient freeness wire insulation                     | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free |
| Amount strands (wire)                                   | 32                                                             |
| Diameter of single wires                                | 0,1 mm                                                         |
| Conductor crosssection (wire)                           | 0,25 mm²                                                       |
| Material conductor wire                                 | Stranded copper wire, bare                                     |
| Conductor type (wire)                                   | strand class 6                                                 |
| Traversing distance (C-track)                           | 10 m @ 25 °C   horizontal                                      |
| Current load capacity (standard)                        | to DIN VDE 0298-4                                              |
| Current load capacity min. wire                         | 3 A                                                            |
| Electrical resistance line constant wire                | 79 Ω/km @ 20 °C                                                |
| Nominal voltage power AC max.                           | 300 V                                                          |
| Power frequency withstand voltage power (wire - jacket) | 2,5 kV @ 60 s                                                  |
| AC withstand voltage power (wire - wire)                | 2,5 kV @ 60 s                                                  |
| Min. operating temperature (static)                     | -40 °C                                                         |
| Max. operating temperature (fixed)                      | 80 °C / 90 °C @ 10000 h Operation                              |
| Operating temperature min. (dynamic)                    | -25 °C                                                         |
| Operating temperature max. (dynamic)                    | 80 °C / 90 °C @ 10000 h Operation                              |
| Flame resistance                                        | IEC 60332-2-2   UL 1581 § 1100 FT2   UL 1581 § 1090            |
| chemical resistance                                     | Good, application-related testing                              |
| Gasoline resistance                                     | Good, application-related testing                              |
| Oil resistance                                          | DIN EN 60811-404   Good, application-related testing           |
| Bending radius (fixed)                                  | 5 x Outer diameter                                             |
| Bending radius (dynamic)                                | 10 x Outer diameter                                            |
| No. of torsion cycles                                   | 2 Mio.                                                         |
| Torsion speed                                           | 35 cycles/min                                                  |
| Torsion stress                                          | ± 180 °/m                                                      |