

Adapter M12 male/ female B-cod. / D-Sub 9-pol. 35°

Shielded, 12Mbit/s

PROFIBUS  
Bus connection plug 35°  
SUB-D9 (male); M12× 1 mm, B-coded  
Programming device

Link naar het product

Afbeelding



Product van afwijken van afbeelding

Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27061801      |
| ECLASS-7.0           | 27061801      |
| ECLASS-8.0           | 27061801      |
| ECLASS-9.0           | 27061801      |
| ECLASS-10.1          | 27242692      |
| ECLASS-11.1          | 27242692      |
| ECLASS-12.0          | 27242692      |
| ETIM-5.0             | EC001855      |
| Douane tarief nummer | 85366990      |
| GTIN                 | 4048879303620 |
| Verpakkingseenheid   | 1             |

Electrical data

|                      |                         |
|----------------------|-------------------------|
| Terminating resistor | connectable, integrated |
|----------------------|-------------------------|

Electrical data | Supply

|                           |         |
|---------------------------|---------|
| Operating voltage DC min. | 4,75 V  |
| Operating voltage DC max. | 5,25 V  |
| Current consumption max.  | 12,5 mA |

Industrial communication

|                             |           |
|-----------------------------|-----------|
| Data transmission rate max. | 12 MBit/s |
|-----------------------------|-----------|

Installation | Connection

|                          |     |
|--------------------------|-----|
| Family construction form | M12 |
|--------------------------|-----|

Device protection | Electrical

|                                     |      |
|-------------------------------------|------|
| Degree of protection (EN IEC 60529) | IP30 |
|-------------------------------------|------|

Mechanical data | Mounting data

|        |       |
|--------|-------|
| Height | 68 mm |
| Width  | 42 mm |
| Depth  | 17 mm |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C  |

**Important installation notes**

|                        |                                                                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note on strain relief  | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                   |
| Note on bending radius | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |