

**Valve plug MDC06-4s / MSUD valve A-18mm Xtreme**

PUR 2x0.75 bk UL/CSA+drag ch. 3m

Xtreme - Outdoor

Male straight – female 90°

6...230 V AC/DC

without components




compatibel to Deutsch DT06-4S


MSUD A

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link naar het product](#)**Afbeelding**



Product van afwijken van afbeelding

|                                     |                   |
|-------------------------------------|-------------------|
| Cable length                        | 3 m               |
| Side 1                              |                   |
| Mounting method                     | inserted, screwed |
| Coating contact                     | nickel plated     |
| Family construction form            | MSUD A            |
| Material contact                    | Copper alloy      |
| No. of poles                        | 4                 |
| Degree of protection (EN IEC 60529) | IP65, IP66K, IP68 |
| Side 2                              |                   |
| Mounting method                     | inserted, screwed |
| Coating contact                     | nickel plated     |
| Family construction form            | Amphenol AT06-4S  |
| Material contact                    | Copper alloy      |
| No. of poles                        | 4                 |
| Degree of protection (EN IEC 60529) | IP68              |
| Commerciële gegevens                |                   |
| ECLASS-6.0                          | 27279218          |
| ECLASS-7.0                          | 27279218          |
| ECLASS-8.0                          | 27279218          |
| ECLASS-9.0                          | 27060311          |
| ECLASS-10.1                         | 27060312          |
| ECLASS-11.1                         | 27060312          |
| ECLASS-12.0                         | 27060312          |
| ETIM-5.0                            | EC001855          |
| Douane tarief nummer                | 85444290          |
| GTIN                                | 4048879908900     |
| Verpakkingseenheid                  | 1                 |
| Electrical data   Supply            |                   |
| Operating voltage AC min.           | 6 V               |
| Operating voltage AC max.           | 230 V             |
| Operating voltage DC min.           | 6 V               |
| Operating voltage DC max.           | 230 V             |
| Current operating per contact max.  | 8 A               |
| Diagnostics                         |                   |
| Status indication LED               | no                |
| Installation   Connection           |                   |

|                                                 |                                                                                                                                                       |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tightening torque                               | 0,4 Nm                                                                                                                                                |
| Mounting set                                    | M3 x 31                                                                                                                                               |
| <b>Device protection   Electrical</b>           |                                                                                                                                                       |
| Pollution Degree                                | 3                                                                                                                                                     |
| Rated surge voltage                             | 4 kV                                                                                                                                                  |
| Material group (IEC 60664-1)                    | I                                                                                                                                                     |
| Additional suppressor                           | without components                                                                                                                                    |
| <b>Mechanical data   Material data</b>          |                                                                                                                                                       |
| Material gasket                                 | Silicon                                                                                                                                               |
| Material housing                                | PA                                                                                                                                                    |
| Material screw connection                       | Stainless steel 1.4305 (V2A)                                                                                                                          |
| <b>Mechanical data   Mounting data</b>          |                                                                                                                                                       |
| Looking techniques                              | Snap-in connector                                                                                                                                     |
| <b>Environmental characteristics   Climatic</b> |                                                                                                                                                       |
| Operating temperature min.                      | -25 °C                                                                                                                                                |
| Operating temperature max.                      | 85 °C                                                                                                                                                 |
| Additional condition temperature range          | depending on cable quality                                                                                                                            |
| <b>Important installation notes</b>             |                                                                                                                                                       |
| Note on strain relief                           | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                   |
| Note on bending radius                          | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |
| <b>Installation   Cable</b>                     |                                                                                                                                                       |
| Cable identification                            | 754                                                                                                                                                   |
| Cable Type                                      | 3                                                                                                                                                     |
| Jacket Color                                    | black                                                                                                                                                 |
| Type of Certificate                             | cURus                                                                                                                                                 |
| Amount stranding                                | 1                                                                                                                                                     |
| Stranding                                       | 2 wires twisted                                                                                                                                       |
| wire arrangement                                | brown, blue                                                                                                                                           |
| Traversing distance (C-track)                   | 10 m @ 25 °C   horizontal                                                                                                                             |
| Cable weighth                                   | 40,7 g/m                                                                                                                                              |
| Material jacket                                 | PUR                                                                                                                                                   |
| Shore hardness jacket                           | 90 ± 5 Shore A                                                                                                                                        |
| Freedom from ingredients (jacket)               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                                                                        |
| Outer-diameter (jacket)                         | 5 mm                                                                                                                                                  |
| Tolerance outer diameter (sheath)               | ± 5 %                                                                                                                                                 |
| Material wire insulation                        | PP                                                                                                                                                    |
| Amount wires                                    | 2                                                                                                                                                     |
| Outer diameter insulation                       | 1,7 mm                                                                                                                                                |
| Outer diameter tolerance core insulation        | ± 5 %                                                                                                                                                 |
| Shore hardness wire insulation                  | 70 ± 5 Shore D                                                                                                                                        |
| Ingredient freeness wire insulation             | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                                                                        |
| Amount strands (wire)                           | 42                                                                                                                                                    |
| Diameter of single wires                        | 0,15 mm                                                                                                                                               |
| Conductor crosssection (wire)                   | 0,75 mm²                                                                                                                                              |
| Material conductor wire                         | Stranded copper wire, bare                                                                                                                            |
| Conductor type (wire)                           | strand class 6                                                                                                                                        |
| Nominal voltage AC max.                         | 300 V                                                                                                                                                 |
| Current load capacity (standard)                | to DIN VDE 0298-4                                                                                                                                     |
| Current load capacity min. wire                 | 12 A                                                                                                                                                  |
| Electrical resistance line constant wire        | 26 Ω/km @ 20 °C                                                                                                                                       |

|                                                   |                                                      |
|---------------------------------------------------|------------------------------------------------------|
| AC withstand voltage (wire - wire)                | 2,5 kV @ 60 s                                        |
| Power frequency withstand voltage (wire - jacket) | 2,5 kV @ 60 s                                        |
| Min. operating temperature (static)               | -40 °C                                               |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                    |
| Operating temperature min. (dynamic)              | -25 °C                                               |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                    |
| UV resistance                                     | DIN EN ISO 4892-2 A                                  |
| Flame resistance                                  | UL 1581 § 1090   UL 1581 § 1100 FT2   IEC 60332-2-2  |
| chemical resistance                               | Good, application-related testing                    |
| Gasoline resistance                               | Good, application-related testing                    |
| Oil resistance                                    | DIN EN 60811-404   Good, application-related testing |
| Bending radius (fixed)                            | 5 x Outer diameter                                   |
| Bending radius (dynamic)                          | 10 x Outer diameter                                  |
| Travel speed (C-track)                            | 10 Mio. @ 25 °C                                      |
| No. of torsion cycles                             | 2 Mio.                                               |
| Torsion stress                                    | ± 180 °/m                                            |
| Torsion speed                                     | 35 cycles/min                                        |