

MODL. VARIO insert for coupling housing type B

8/6 shut-off, dezincification resistant brass

Modlink Vario  
Brass, dezincification-resistant  
with shut-off  
AD8

Link naar het product

Afbeelding



Product van afwijken van afbeelding

Commerciële gegevens

|                      |               |
|----------------------|---------------|
| ECLASS-6.0           | 27260702      |
| ECLASS-6.1           | 27260708      |
| ECLASS-7.0           | 27440312      |
| ECLASS-8.0           | 27440312      |
| ECLASS-9.0           | 27440312      |
| ECLASS-10.1          | 27440312      |
| ECLASS-11.1          | 27440312      |
| ECLASS-12.0          | 27440312      |
| ETIM-5.0             | EC002641      |
| Douane tarief nummer | 74198090      |
| GTIN                 | 4048879574303 |
| Verpakkingseenheid   | 1             |

Device protection | Electrical

|                                        |                   |
|----------------------------------------|-------------------|
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68  |
| Degree of protection (ISO 20653:2013)  | IP66K, IP69K      |
| Additional condition protection degree | inserted, screwed |

Mechanical data

|                         |               |
|-------------------------|---------------|
| Barrier                 | with shut-off |
| Operating pressure min. | 0 bar         |
| Operating pressure max. | 16 bar        |

Mechanical data | Material data

|                  |       |
|------------------|-------|
| Material gasket  | FPM   |
| Material housing | Brass |

Mechanical data | Mounting data

Outer diameter hose 8 mm

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 120 °C |